

911 SIGNAL®



BLAZERS


TECHNICAL SPECIFICATIONS

Item	091401, 091406
Voltage	DC 10-33V
Max Power	30W
Frequency	200-1600HZ
Sound Distortion	≤5%
Sound Intensity	≥ 100dB/2m
Siren Tones	30
Certification	ECE R10 05 01 16737, TP SPO 12116, TP ASA 12118, TP UMH 12117, TP POL 12114, TP GN 12115

FEATURES

- 10-33V multi-voltage input, multiple speakers work synchronously to improve the sound intensity and a function to decrease the volume at night, meet requirements for sound output;
- An output integration of amplifier, speaker and lighting control, compact design for simple installation and space saving;
- 30 programmable siren tones for versatile needs in different regions and industries.
- Supports external microphones (optional)
- Supports up to 8amp warning light, the external warning light operates synchronously with the siren.
- A separate input control line allows individual on/off control over the warning light.

WIRING




Note: There are no pre-set tones




WARNING!

Do not connect GRN/WHI wire to the positive terminal of the battery.

DIMENSIONS



MOUNT



SIREN TONES

1	Wail
2	Yelp
3	Piercer
4	Airhorn
5	Hi/Low
6	China police
7	China ambulance
8	France-Police
9	France-Gendarmerie
10	France-Sapeurs-Pompiers
11	France-ASA
12	France-UHM
13	Italia ambulance
14	Italia Police
15	Fire Brigade (Italy and Czech Republic)
16	Yelp*249
17	POWERCALL
18	UNITROL-ULTRAHILO
19	UNITROL-HERTRO
20	Hi/Low 466p
21	Horn
22	Wail (SUBTONE)
23	Yelp (SUBTONE)
24	Piercer (SUBTONE)
25	Airhorn (SUBTONE)
26	Hi/Low (SUBTONE)
27	POWERCALL (SUBTONE)
28	UNITROL ULTRAHILO (SUBTONE)
29	UNITROL HERTRO (SUBTONE)
30	Manual

911 Signal Technology Inc.

Add:Room 701-702,Hengwei Building,No.258, Tiangao Lane,
Shounan Subdistrict,Yinzhou Area,Ningbo City,
Zhejiang,China.

Tel: +86 574 89017911 +86 400 6757911

Fax: +86 574 82822560

Email: sales@911signal.com

Website: www.911signal.com



Please wear hearing protection equipment, for loud sound
may damage hearing ability.

